

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2020/878 - Europe

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Hempadur Fast Dry 17419 Base
Product identity : 1741912170
Product type : hi-build epoxy paint (base for multi-component product)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : metal industry, ships and shipyards.
Ready-for-use mixture : 17410 = 17419 4 vol. / 98410 1 vol.
Identified uses : Industrial applications, Professional applications, Used by spraying.

1.3 Details of the supplier of the safety data sheet

Company details : HEMPEL A/S
Lundtoftegårdsvej 91
DK-2800 Kgs. Lyngby
Denmark
Tel.: + 45 45 93 38 00
hempel@hempel.com
Date of issue : 18 November 2022
Date of previous issue : 6 April 2022.

1.4 Emergency telephone number

Emergency telephone number (with hours of operation)

+45 45 93 38 00 (08.00 - 17.00)
See section 4 First aid measures.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture


Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226 FLAMMABLE LIQUIDS
Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION
Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION
Skin Sens. 1, H317 SKIN SENSITIZATION
Aquatic Chronic 3, H412 AQUATIC HAZARD (LONG-TERM)

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning
Hazard statements : H226 - Flammable liquid and vapor.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention : Wear protective gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hazardous ingredients : Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700
middle molecular epoxy resin MMW 700-1200
Methylstyrenated phenol
1,3-bis(12-hydroxyocta-decanamide-N-methyle)benzene

Supplemental label elements : Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Contains epoxy constituents. May produce an allergic reaction.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.
Tactile warning of danger : Not applicable.

SECTION 2: Hazards identification

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

| Product/ingredient name | Identifiers | % | Regulation (EC) No. 1272/2008 [CLP] | Type | |
|---|--|-----------|--|--|-------------|
| epi-phenol A-(epichlorhydrin) epoxy resin MW =< 700 | REACH #: 01-2119456619-26 EC: 500-033-5 CAS: 1675-54-3 Index: 603-074-00-8 | ≥10 - ≤14 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 | Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5% | [1] |
| xylene | REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9 | ≥5 - ≤10 | Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 | ATE [Dermal] = 1100 mg/kg ATE [Inhalation (gases)] = 5000 ppm | [1] [2] |
| middle molecular epoxy resin MMW 700-1200 | EC: 500-033-5 CAS: 25068-38-6 | ≥5 - ≤10 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 | Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5% | [1] |
| titanium dioxide | REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7 Index: 022-006-00-2 | ≥3 - ≤5 | Carc. 2, H351 (inhalation) | - | [1] [*] |
| Methylstyrenated phenol | REACH #: 01-2119555274-38 EC: 270-966-8 CAS: 68512-30-1 | ≥3 - ≤5 | Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 3, H412 | - | [1] |
| butan-1-ol | REACH #: 01-2119484630-38 EC: 200-751-6 CAS: 71-36-3 Index: 603-004-00-6 | ≥1 - <3 | Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336 | ATE [Oral] = 790 mg/kg | [1] |
| ethylbenzene | REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4 | ≥1 - ≤3 | Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | ATE [Inhalation (vapours)] = 11 mg/l M [Acute] = 1 M [Chronic] = 1 | [1] [2] |
| trizinc bis(orthophosphate) | REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6 | ≤0.93 | Skin Sens. 1B, H317 Aquatic Chronic 4, H413 | - | [1] |
| 1,3-bis(12-hydroxyoctadecanamide-N-methyle) benzene | REACH #: 01-0000016979-49 EC: 423-300-7 | <1 | Skin Sens. 1B, H317 Aquatic Chronic 4, H413 | - | [1] |
| toluene | REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3 | ≤0.3 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 | - | [1] [2] |
| 4,4'-isopropylidenediphenol | REACH #: 01-2119457856-23 EC: 201-245-8 CAS: 80-05-7 Index: 604-030-00-0 | ≤0.015 | Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360F STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | M [Acute] = 1 M [Chronic] = 10 | [1] [2] [3] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit, see section 8.

[3] Substance of equivalent concern

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

SECTION 4: First aid measures

4.1 Description of first aid measures

| | |
|------------------------------|---|
| General : | In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid). |
| Eye contact : | Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention. |
| Inhalation : | Remove to fresh air. Keep person warm and at rest. If unconscious, place in recovery position and seek medical advice. |
| Skin contact : | Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. |
| Ingestion : | If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat. |
| Protection of first-aiders : | No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

| | |
|----------------|--|
| Eye contact : | Causes serious eye irritation. |
| Inhalation : | No known significant effects or critical hazards. |
| Skin contact : | Causes skin irritation. May cause an allergic skin reaction. |
| Ingestion : | No known significant effects or critical hazards. |

Over-exposure signs/symptoms

| | |
|----------------|--|
| Eye contact : | Adverse symptoms may include the following: pain or irritation watering redness |
| Inhalation : | No specific data. |
| Skin contact : | Adverse symptoms may include the following: irritation redness |
| Ingestion : | No specific data. |

4.3 Indication of any immediate medical attention and special treatment needed

| | |
|-----------------------|---|
| Notes to physician : | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments : | No specific treatment. |

SECTION 5: Firefighting measures

5.1 Extinguishing media

| | |
|-----------------------|---|
| Extinguishing media : | Recommended: alcohol resistant foam, CO ₂ , powders, water spray. Not to be used: waterjet. |
|-----------------------|---|

5.2 Special hazards arising from the substance or mixture

| | |
|---|---|
| Hazards from the substance or mixture : | Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
| Hazardous combustion products : | Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides |

5.3 Advice for firefighters

SECTION 5: Firefighting measures

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.

6.3 Methods and materials for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used. Contains epoxy constituents. Avoid all possible skin contact with epoxy and amine containing products, they may cause allergic reactions.

Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Product/ingredient name | Exposure limit values |
|-------------------------|---|
| xylene | EU OEL (Europe, 1/2022). [xylene, mixed isomers] Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 221 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m ³ 15 minutes. |
| ethylbenzene | EU OEL (Europe, 1/2022). Absorbed through skin. STEL: 884 mg/m ³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 442 mg/m ³ 8 hours. TWA: 100 ppm 8 hours. |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------------------|---|
| toluene | EU OEL (Europe, 1/2022). Absorbed through skin. TWA: 192 mg/m ³ 8 hours. TWA: 50 ppm 8 hours. STEL: 384 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. |
| 4,4'-isopropylidenediphenol | EU OEL (Europe, 1/2022). TWA: 2 mg/m ³ 8 hours. Form: Inhalable fraction |

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived effect levels

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|--|------|----------------------|-------------------------|------------|----------|
| Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 | DNEL | Long term Dermal | 8.33 mg/kg bw/day | Workers | Systemic |
| xylene | DNEL | Long term Inhalation | 12.25 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Inhalation | 77 mg/m ³ | Workers | Systemic |
| Methylstyrenated phenol | DNEL | Long term Dermal | 180 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Dermal | 3.5 mg/kg bw/day | Workers | Systemic |
| ethylbenzene | DNEL | Long term Inhalation | 1.4 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 180 mg/kg bw/day | Workers | Systemic |
| trizinc bis(orthophosphate) | DNEL | Long term Inhalation | 77 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Inhalation | 5 mg/m ³ | Workers | Systemic |
| toluene | DNEL | Long term Dermal | 83 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Dermal | 384 mg/kg bw/day | Workers | Systemic |
| 4,4'-isopropylidenediphenol | DNEL | Long term Inhalation | 192 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 0.031 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 2 mg/m ³ | Workers | Systemic |

Predicted effect concentrations

| Product/ingredient name | Compartment Detail | Value | Method Detail |
|--|------------------------|-----------------|---------------|
| Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 | Fresh water | 0.006 mg/l | - |
| | Marine | 0.0006 mg/l | - |
| | Sewage Treatment Plant | 10 mg/l | - |
| | Fresh water sediment | 0.996 mg/l | - |
| xylene | Marine water sediment | 0.0996 mg/l | - |
| | Soil | 0.196 mg/l | - |
| | Fresh water | 0.327 mg/l | - |
| | Marine water | 0.327 mg/l | - |
| | Fresh water sediment | 12.46 mg/kg | - |
| | Marine water sediment | 12.46 mg/kg | - |
| | Soil | 2.31 mg/kg | - |
| Methylstyrenated phenol | Sewage Treatment Plant | 6.68 mg/l | - |
| | Sewage Treatment Plant | 2.4 mg/l | - |
| | Fresh water | 14 µg/l | - |
| | Marine | 1.4 µg/l | - |
| ethylbenzene | Fresh water sediment | 1064 mg/kg dwt | - |
| | Marine water sediment | 106 mg/kg dwt | - |
| | Soil | 212 mg/kg dwt | - |
| | Fresh water | 0.1 mg/l | - |
| | Marine water | 0.01 mg/l | - |
| trizinc bis(orthophosphate) | Sewage Treatment Plant | 9.6 mg/l | - |
| | Fresh water sediment | 13.7 mg/kg | - |
| | Soil | 2.68 mg/kg | - |
| | Fresh water | 20.6 µg/l | - |
| | Marine water | 6.1 µg/l | - |
| toluene | Fresh water sediment | 117.8 mg/kg dwt | - |
| | Marine water sediment | 56.5 mg/kg dwt | - |
| | Soil | 35.6 mg/kg dwt | - |
| | Sewage Treatment Plant | 52 µg/l | - |
| | Fresh water | 0.68 mg/l | - |
| | Marine water | 0.68 mg/l | - |
| | Sewage Treatment Plant | 13.61 mg/l | - |

SECTION 8: Exposure controls/personal protection

| | | | |
|-------------|------------------------|------------------|---|
| phenol | Fresh water sediment | 16.39 mg/kg | - |
| | Marine water sediment | 16.39 mg/kg | - |
| | Soil | 2.89 mg/kg | - |
| | Fresh water | 0.0077 mg/l | - |
| | Marine water | 0.00077 mg/l | - |
| bisphenol A | Sewage Treatment Plant | 2.1 mg/l | - |
| | Fresh water sediment | 0.0915 mg/kg | - |
| | Marine water sediment | 0.00915 mg/kg | - |
| | Soil | 0.36 mg/kg | - |
| | Fresh water | 0.018 mg/l | - |
| methanol | Marine water | 0.016 mg/l | - |
| | Sewage Treatment Plant | 320 mg/l | - |
| | Sediment | 1.2 mg/kg | - |
| | Soil | 3.7 mg/kg | - |
| | Fresh water | 0.062 mg/l | - |
| | Marine water | 0.0062 mg/l | - |
| | Fresh water sediment | 0.22 mg/kg dwt | - |
| | Marine water sediment | 0.022 mg/kg dwt | - |
| methanol | Soil | 0.0085 mg/kg dwt | - |
| | Sewage Treatment Plant | 25 mg/l | - |

8.2 Exposure controls

Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Individual protection measures

- General :** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.
- Hygiene measures :** Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.
- Eye/face protection :** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Hand protection :** Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.
Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:

Recommended: Silver Shield / Barrier / 4H gloves, polyvinyl alcohol (PVA), Viton®
May be used: nitrile rubber, butyl rubber
Short term exposure: neoprene rubber, natural rubber (latex), polyvinyl chloride (PVC)
- Body protection :** Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.
Wear suitable protective clothing. Always wear protective clothing when spraying.
- Respiratory protection :** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If working areas have insufficient ventilation: When the product is applied by means that will not generate an aerosol such as, brush or roller wear half or totally covering mask equipped with gas filter of type A, when grinding use particle filter of type P. Be sure to use an approved/certified respirator or equivalent.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---|
| Physical state : | Liquid. |
| Color : | Gray |
| Odor : | Solvent-like |
| pH : | Testing not relevant or not possible due to nature of the product. |
| Melting point/freezing point : | 1339°C This is based on data for the following ingredient: Calcium carbonate |
| Boiling point/boiling range : | Testing not relevant or not possible due to nature of the product. |
| Flash point : | Closed cup: 26°C (78.8°F) [Setaflash] |
| Evaporation rate : | Testing not relevant or not possible due to nature of the product. |
| Flammability : | Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat. |
| Lower and upper explosive (flammable) limits : | 0.8 - 11.3 vol % |
| Vapor pressure : | Testing not relevant or not possible due to nature of the product. |
| Vapor density : | Testing not relevant or not possible due to nature of the product. |
| Specific gravity : | 1.708 g/cm ³ |
| Partition coefficient (LogKow) : | Testing not relevant or not possible due to nature of the product. |
| Auto-ignition temperature : | Lowest known value: 355°C (671°F) (butan-1-ol). |
| Decomposition temperature : | Testing not relevant or not possible due to nature of the product. |
| Viscosity : | Aspiration hazard (H304) Not classified. Testing not relevant due to nature of the product. |
| Explosive properties : | Explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat. |
| Oxidizing properties : | Testing not relevant or not possible due to nature of the product. |

9.2 Other information

| | |
|--------------------------------------|---|
| Solvent(s) % by weight : | Weighted average: 14 % |
| Water % by weight : | Weighted average: 0 % |
| VOC content : | 234.7 g/l |
| VOC content, Ready-for-use mixture : | 245.1 g/l |
| TOC Content : | Weighted average: 198 g/l |
| Solvent Gas : | Weighted average: 0.059 m ³ /l |

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is stable.

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials

Highly reactive or incompatible with the following materials: oxidizing materials.
Reactive or incompatible with the following materials: reducing materials.

10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

SECTION 10: Stability and reactivity

Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to component solvent vapor concentrations may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Accidental swallowing may cause stomach pain. Chemical lung inflammation may occur if the product is taken into the lungs via vomiting.

Epoxy and amine containing products can cause skin disorders such as allergic eczema. The allergy may arise after only a short exposure period.

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|---------------------------------|---------|-------------------------|----------|
| Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 | LD50 Dermal | Rabbit | >2000 mg/kg | - |
| | LD50 Dermal | Rat | >2000 mg/kg | - |
| xylene | LD50 Oral | Rat | >2000 mg/kg | - |
| | LC50 Inhalation Gas. | Rat | 5000 ppm | 4 hours |
| | LC50 Inhalation Vapor | Rat | 6350 ppm | 4 hours |
| | LD50 Dermal | Rabbit | >4200 mg/kg | - |
| middle molecular epoxy resin MMW 700-1200 | LD50 Oral | Rat | 3523 mg/kg | - |
| | LD50 Dermal | Rat | >2000 mg/kg | - |
| titanium dioxide | LC50 Inhalation Dusts and mists | Rat | >6.8 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| Methylstyrenated phenol | LC50 Inhalation Dusts and mists | Rat | >5 mg/l | 4 hours |
| | LD50 Dermal | Rat | >2000 mg/kg | - |
| butan-1-ol | LC50 Inhalation Vapor | Rat | 24000 mg/m ³ | 4 hours |
| | LD50 Dermal | Rabbit | 3400 mg/kg | - |
| | LD50 Oral | Rat | 790 mg/kg | - |
| ethylbenzene | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| | LD50 Oral | Rat | 3500 mg/kg | - |
| trizinc bis(orthophosphate) 1,3-bis(12-hydroxyoctadecanamide-N-methyle)benzene | LD50 Oral | Rat | >5000 mg/kg | - |
| | LC50 Inhalation Dusts and mists | Rat | >5 mg/m ³ | 4 hours |
| toluene | LD50 Dermal | Rat | >2000 mg/kg | - |
| | LD50 Oral | Rat | >2000 mg/kg | - |
| | LC50 Inhalation Vapor | Rat | >20 mg/l | 4 hours |
| 4,4'-isopropylidenediphenol | LD50 Oral | Rat | 636 mg/kg | - |
| | LD50 Dermal | Rabbit | >2000 mg/kg | - |
| | LD50 Oral | Rat | 3250 mg/kg | - |
| | LD50 Oral | Rat | 3250 mg/kg | - |

Acute toxicity estimates

| Product/ingredient name | Oral mg/kg | Dermal mg/kg | Inhalation (gases) ppm | Inhalation (vapors) mg/l | Inhalation (dusts and mists) mg/l |
|--|------------|--------------|------------------------|--------------------------|-----------------------------------|
| Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 | 27172.8 | 12893.2 | 58605.3 | 581.3 | |
| xylene | 3523 | 1100 | 5000 | | |
| butan-1-ol | 790 | 3400 | | 24 | |
| ethylbenzene | 3500 | | | 11 | |
| 4,4'-isopropylidenediphenol | 3250 | | | | |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure |
|--|--------------------------|---------|-------|--------------------------------------|
| Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 | Eyes - Mild irritant | Rabbit | - | - |
| | Skin - Mild irritant | Rabbit | - | - |
| xylene | Eyes - Severe irritant | Rabbit | - | 24 hours 5 milligrams |
| | Skin - Irritant | Rabbit | - | - |
| titanium dioxide | Skin - Moderate irritant | Rabbit | - | 24 hours 500 milligrams |
| | Skin - Mild irritant | Human | - | 72 hours 300 Micrograms Intermittent |
| Methylstyrenated phenol | Eyes - Mild irritant | Rabbit | - | - |
| | Skin - Irritant | Rabbit | - | - |
| butan-1-ol | Eyes - Severe irritant | Rabbit | - | 24 hours 2 milligrams |

SECTION 11: Toxicological information

| | | | | |
|-----------------------------|-----------------------------|--------|---|----------------------------|
| ethylbenzene | Skin - Moderate irritant | Rabbit | - | 24 hours 20 milligrams |
| | Eyes - Mild irritant | Rabbit | - | - |
| | Respiratory - Mild irritant | Rabbit | - | - |
| toluene | Skin - Mild irritant | Rabbit | - | 24 hours 15 milligrams |
| | Eyes - Mild irritant | Rabbit | - | 0.5 minutes 100 milligrams |
| 4,4'-isopropylidenediphenol | Skin - Moderate irritant | Rabbit | - | 24 hours 20 milligrams |
| | Eyes - Severe irritant | Rabbit | - | 24 hours 250 Micrograms |
| | Skin - Mild irritant | Rabbit | - | 24 hours 500 milligrams |

Sensitizer

| Product/ingredient name | Route of exposure | Species | Result |
|--|-------------------|------------|-------------|
| Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 | skin | Guinea pig | Sensitizing |
| middle molecular epoxy resin MMW 700-1200 | skin | Guinea pig | Sensitizing |

Mutagenic effects

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Reproductive toxicity

No known significant effects or critical hazards.

Teratogenic effects

No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-----------------------------|------------|-------------------|--|
| Butan-1-ol | Category 3 | | Respiratory tract irritation |
| toluene | Category 3 | | Narcotic effects |
| 4,4'-isopropylidenediphenol | Category 3 | | Narcotic effects Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|----------------|
| ethylbenzene | Category 2 | - | hearing organs |
| toluene | Category 2 | - | - |

Aspiration hazard

| Product/ingredient name | Result |
|-------------------------|--------------------------------|
| ethylbenzene | ASPIRATION HAZARD - Category 1 |
| toluene | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential chronic health effects

Sensitization : Contains bisphenol A-(epichlorhydrin) epoxy resin MW =< 700, middle molecular epoxy resin MMW 700-1200, Methylstyrenated phenol, 1,3-bis(12-hydroxyocta-decanamide-N-methyle)benzene. May produce an allergic reaction.

11.2 Information on other hazards

Endocrine disrupting properties : See Section 15 for details.

Other information : No additional known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Do not allow to enter drains or watercourses. Harmful to aquatic life with long lasting effects.

SECTION 12: Ecological information

| Product/ingredient name | Result | Species | Exposure |
|---|---|--|---|
| Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 | Acute EC50 >11 mg/l | Algae | 72 hours |
| | Acute EC50 1.8 mg/l Acute LC50 2 mg/l | Daphnia Fish | 48 hours 96 hours |
| middle molecular epoxy resin MMW 700-1200 | Acute EC50 >100 mg/l | Daphnia | 48 hours |
| titanium dioxide | Acute LC50 >100 mg/l Acute LC50 >100 mg/l | Fish Daphnia | 96 hours 48 hours |
| Methylstyrenated phenol | Acute EC50 15 mg/l Acute EC50 14 - 51 mg/l | Algae Daphnia | 72 hours 48 hours |
| butan-1-ol | Acute EC50 25.8 mg/l Acute EC50 1328 mg/l | Fish Daphnia | 96 hours 96 hours |
| ethylbenzene | Acute LC50 1.376 mg/l | Fish | 96 hours |
| trizinc bis(orthophosphate) | Chronic NOEC <1000 µg/l Fresh water Acute EC50 0.8 mg/l | Algae - Pseudokirchneriella subcapitata Algae | 96 hours 72 hours |
| 1,3-bis(12-hydroxyocta-decanamide-N-methyle)benzene | Acute EC50 2.44 mg/l Acute LC50 >100 mg/l | Daphnia Algae | 48 hours 72 hours |
| toluene | Acute LC50 >100 mg/l Chronic NOEC <500000 µg/l Fresh water | Fish Algae - Pseudokirchneriella subcapitata | 96 hours 96 hours |
| 4,4'-isopropylidenediphenol | Chronic NOEC 1000 µg/l Fresh water Acute LC50 7.5 mg/l Chronic NOEC 0.8 mg/l Fresh water Chronic NOEC 0.2 - 20 ppb Fresh water | Daphnia - Daphnia magna Fish Daphnia - Daphnia magna - Neonate Fish - Xiphophorus helleri - Juvenile (Fledgling, Hatchling, Weanling) | 21 days 96 hours 21 days 60 days |

12.2 Persistence and degradability

| Product/ingredient name | Test | Result | Dose | Inoculum |
|---|---|---------------------------------|------|----------|
| Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 | OECD 302B Inherent Biodegradability: Zahn-Wellens/EMPA Test | 12 % - Not readily - 28 days | - | - |
| xylene | OECD 301F Ready Biodegradability - Manometric Respirometry Test | 90 - 98 % - Readily - 28 days | - | - |
| butan-1-ol | - | >60 % - Readily - 28 days | - | - |
| ethylbenzene | OECD 301D Ready Biodegradability - Closed Bottle Test | 92 % - 20 days | - | - |
| 1,3-bis(12-hydroxyocta-decanamide-N-methyle)benzene | - | >70 % - Readily - 28 days | - | - |
| toluene | - | 5 % - 28 days | - | - |
| 4,4'-isopropylidenediphenol | - | 100 % - Readily - 14 days | - | - |
| | | 1 - 2 % - Not readily - 28 days | - | - |

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 | - | - | Not readily |
| xylene | - | - | Readily |
| Methylstyrenated phenol | - | - | Not readily |
| butan-1-ol | - | - | Readily |
| ethylbenzene | - | - | Readily |
| 1,3-bis(12-hydroxyocta-decanamide-N-methyle)benzene | - | - | Not readily |
| toluene | - | - | Readily |
| 4,4'-isopropylidenediphenol | - | - | Not readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|--|--------------------|------------|-----------|
| Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 | 2.64 - 3.78 | 31 | low |
| xylene | 3.12 | 8.1 - 25.9 | low |
| middle molecular epoxy resin MMW 700-1200 | 2.64 - 3.78 | 31 | low |
| Methylstyrenated phenol | 3.627 | - | low |
| butan-1-ol | 1 | 3.16 | low |
| ethylbenzene | 3.6 | - | low |
| trizinc bis(orthophosphate) | - | 60960 | high |
| toluene | 2.73 | 90 | low |
| 4,4'-isopropylidenediphenol | 3.4 | 20 - 67 | low |

SECTION 12: Ecological information

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}): No known data available in our database.

Mobility: No known data available in our database.

12.5 Results of PBT and vPvB assessment

| Product/ingredient name | PBT | P | B | T | vPvB | vP | vB |
|---|-----|---|---|---|------|----|----|
| This mixture does not contain any substances that are assessed to be a PBT or a vPvB. | | | | | | | |

12.6 Endocrine disrupting properties

See Section 15 for details.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

European waste catalogue no. (EWC) is given below.




European waste catalogue (EWC) : 08 01 11*

Packaging

The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

Transport may take place according to national regulation or ADR for transport by road, RID for transport by train, IMDG for transport by sea, IATA for transport by air.

| | 14.1 UN / ID no. | 14.2 Proper shipping name | 14.3 Transport hazard class(es) | 14.4 PG* | 14.5 Env* | Additional information |
|----------------------|---------------------|------------------------------|--|-------------|--------------|--|
| ADR/RID Class | UN1263 | PAINT | 3  | III | No. | Tunnel code (D/E) |
| IMDG Class | UN1263 | PAINT | 3  | III | No. | Emergency schedules F-E, S-E |
| IATA Class | UN1263 | PAINT | 3  | III | No. | - |

PG* : Packing group

Env.* : Environmental hazards

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization - Substances of very high concern

Annex XIV

None of the components are listed.

Substances of very high concern

| Ingredient name | Intrinsic property | Status | Reference number | Date of revision |
|-----------------------------|--|-------------|------------------|------------------|
| 4,4'-isopropylidenediphenol | Toxic to reproduction | Recommended | ED/01/2018 | 10/1/2019 |
| 4,4'-isopropylidenediphenol | Endocrine disrupting properties for human health | Recommended | ED/01/2018 | 10/1/2019 |
| 4,4'-isopropylidenediphenol | Endocrine disrupting properties for environment | Recommended | ED/01/2018 | 10/1/2019 |

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

Other EU regulations

Seveso category This product is controlled under the Seveso III Directive.

| Seveso category |
|---|
| P5c: Flammable liquids 2 and 3 not falling under P5a or P5b |

15.2 Chemical Safety Assessment

SECTION 16: Other information

Abbreviations and acronyms :

ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 EUH statement = CLP-specific Hazard statement
 RRN = REACH Registration Number
 DNEL = Derived No Effect Level
 PNEC = Predicted No Effect Concentration

Full text of abbreviated H statements :

H225 Highly flammable liquid and vapor.
 H226 Flammable liquid and vapor.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.
 H360F May damage fertility.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.

Full text of classifications [CLP/GHS] :

Acute Tox. 4 ACUTE TOXICITY - Category 4
 Aquatic Acute 1 AQUATIC HAZARD (ACUTE) - Category 1
 Aquatic Chronic 1 AQUATIC HAZARD (LONG-TERM) - Category 1
 Aquatic Chronic 2 AQUATIC HAZARD (LONG-TERM) - Category 2
 Aquatic Chronic 3 AQUATIC HAZARD (LONG-TERM) - Category 3
 Aquatic Chronic 4 AQUATIC HAZARD (LONG-TERM) - Category 4
 Asp. Tox. 1 ASPIRATION HAZARD - Category 1
 Carc. 2 CARCINOGENICITY - Category 2
 Eye Dam. 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
 Eye Irrit. 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
 Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2
 Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3
 Repr. 1B TOXIC TO REPRODUCTION - Category 1B
 Repr. 2 TOXIC TO REPRODUCTION - Category 2
 Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2
 Skin Sens. 1 SKIN SENSITIZATION - Category 1

SECTION 16: Other information

Skin Sens. 1B SKIN SENSITIZATION - Category 1B
STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|------------------------------------|-----------------------|
| FLAMMABLE LIQUIDS | On basis of test data |
| SKIN CORROSION/IRRITATION | Calculation method |
| SERIOUS EYE DAMAGE/ EYE IRRITATION | Calculation method |
| SKIN SENSITIZATION | Calculation method |
| AQUATIC HAZARD (LONG-TERM) | Calculation method |

Notice to reader

➤ Indicates information that has changed from previously issued version.

The information contained in this safety data sheet is based on the present state of knowledge and EU and national legislation. It provides guidance on health, safety and environmental aspects for handling the product in a safe way and should not be construed as any guarantee of the technical performance or suitability for particular applications.

It is always the duty of the user/employer to ascertain that the work is planned and carried out in accordance with the national regulations.

Safe Use of Mixture Information

Hempadur Fast Dry 17419 Base



This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

Indoor or outdoor spray painting by professionals or with brush, roller, putty knife, dipping etc. with good general room ventilation

This safe use information is linked to : Professional spray painting and/or low-energy painting, local effect - Level II
Skin Sens. 1, Eye Irrit. 2 , Asp. Tox. 1 or Solvent.

Sector(s) of use : Industrial uses - Professional uses

Product category(ies) : Coatings and paints, thinners, paint removers

Operational conditions

Place of use : Indoor or outdoor use

Risk management measures (RMM)

| Contributing activity | Process category (ies) | Maximum duration | Ventilation | | Respiratory | Eye | Hands |
|---|------------------------|-------------------|--|-------|--|---|---------------------------------------|
| | | | Type and air changes per hour | | | | |
| Preparation of material for application | PROC05 | More than 4 hours | Good general room ventilation - Outdoors | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Loading of application equipment and handling of coated parts before curing | PROC08a | More than 4 hours | Good general room ventilation - Outdoors | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Professional application of coatings by brush or roller | PROC10 | More than 4 hours | Good general room ventilation - Outdoors | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Professional application of coatings by spraying | PROC11 | More than 4 hours | Good general room ventilation - Outdoors | 3 - 5 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Film formation - force drying, stoving and other technologies | PROC04 | More than 4 hours | Good general room ventilation - Outdoors | 3 - 5 | None | None | None |
| Cleaning | PROC05 | More than 4 hours | Good general room ventilation - Outdoors | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Waste management | PROC08a | More than 4 hours | Good general room ventilation - Outdoors | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |

See chapter 8 of this Safety Data Sheet for specifications.

